

technical specifications

VK-IPC-B251-AS-LI



5 MP
2.8 mm



smart dual light
IR and white light



perimeter protection
SMD



IP67
metal case

Camera

Image sensor	1/2.7" CMOS
Max. resolution	5 MP, 2880 (H) x 1620 (V)
Electronic shutter	Auto / Manual 1/3 s - 1/100,000 s
Min. illumination	0.006Lux / 0Lux (Illuminator on)
S/N Ratio	> 56 dB
Illumination distance	IR light 50 m / white light 50 m
Illuminator control	Auto/Manual

Lens

Lens type	Fixed-focal
Focal length	2.8 mm
Max. aperture	F/1.6
Field of view	H: 111° / V: 59° / D: 134°
Iris type	Auto

Video

Compression	H.264H/H.264M/H.264B/H.265
Smart compression	H.264H+/H.264M+/H.264B+/H.265+
Video frame rate	Main Stream: 5 MP (1 fps~25/30 fps) Sub Stream: D1 (1 fps~25/30 fps) Third Stream: 720P (1 fps~25/30 fps)
Bit rate control	CBR/VBR
Video bit rate	H.264: 3 Kbps~20480 Kbps H.265: 3 Kbps~20480 Kbps
Day/Night	Color/B/W
BLC	Yes
HLC	Yes
AWB	Yes
AGC	Auto/Manual
WDR	DWDR

Motion detection	OFF/ON (4 areas, rectangular)
Noise reduction	3D NR
Image rotation	180°
Mirror	Yes
Privacy masking	4 areas

Intelligence

Smart motion detection	Yes
Perimeter protection	Intrusion, tripwire (Support the classification of Vehicle / Human / Non-Motor)
AI search	Works together with NVR

Audio

Built-in mic	Yes
--------------	-----

Alarm




Arming / disarming	Yes
Alarm event	network disconnection; IP conflict, no SD card, capacity warning, SD card error

Network

Network	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network protocol	TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP, DNS, DDNS, FTP, NTP, PPPOE, UPNP, SMTP
Interoperability	ONVIF, CGI, P2P (Q2 2025)
User/Host	20 (total bandwidth: 80 M)
Storage	FTP, micro SD card (support max. 256G)
Browser	IE8 and later, Chrome, Firefox

General

Power supply	12V DC ($\pm 30\%$) / PoE (802.3af)
Power consumption	Basic: 2.8W / Max.: 5.5W
Operating conditions	-30°C to $+60^{\circ}\text{C}$ / Less than 95% RH
Storage conditions	-40°C to $+60^{\circ}\text{C}$
Protection grade	IP67
Casing	Metal
Dimensions	224 mm $\times$ 77 mm $\times$ 76 mm



Accessories (not included):



VK-BOX-B3
VK-BOX-B3-B

Available models:
VK-IPC-B251-AS-LI
VK-IPC-B251-AS-LI-B